

“CMC-ETL-700-300” Equipment Transfer Lock



“CLOSED” CONFIGURATION



“OPENED” CONFIGURATION

PRESENTATION

Certification	DNV
Operating pressure	30 bar
Internal diameter	Ø 700 mm
Internal length (can be adjusted on demand)	700 mm
Outer operating temperature	-10 °C to +50 °C

TRANSFER OF EQUIPMENT SUCH AS

Consumables	Soda lime, water , etc.
Miscellaneous components	Diving tools, lift bags, etc.

CONNECTION TO HYPERBARIC CHAMBER

Type	Flange
Number of M36 studs	24

NOZZLES ON CYLINDRICAL SHELL

Number	3
--------	---

USE

1” NPT	Exhaust
1/2” NPT	Pressurisation
1/4” NPT	Pressure tap

CLAMP OPERATION

Normal	Hydraulic
Emergency	Manual action
Safety	Interlock

TRANSPORTATION

Weight	377 kg
Means of lifting	Slings

CMC Industries

ZI la Grande Marine - BP 90033
84 801 L'Isle Sur La Sorgue cedex
FRANCE

Tel. + 33 (0) 490 382 722
Fax. + 33 (0) 490 383 819
www.cmc-industries.com

Contact: Eric Guillermet
Mobile phone: + 33 (0) 680 062 202
Contact: Jean-Pierre Déchaut
Mobile phone: + 33 (0) 665 403 151

